

Metric Standard



Номер детали	Материал кольца	ID	OD	Width	Тип щита	Динамическая нагрузка	Статическая нагрузка	Ограниченная скорость (x1K об/мин)	Система измерений	Тип подшипника	Тип шарикоподшипника	Construction	Precision	Clearance	Температурный диапазон	RoHS	SGS
689zz	52100 Chrome Steel	9 mm	17 mm	5 mm	Shielded	1128 N	534 N	36	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S689 2rs	440C Stainless Steel	9 mm	17 mm	5 mm	Sealed	1015 N	481 N	32.4	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
689 2rs	52100 Chrome Steel	9 mm	17 mm	5 mm	Sealed	1128 N	534 N	36	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S689	440C Stainless Steel	9 mm	17 mm	4 mm	Open	1015 N	481 N	32.4	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S679zz	440C Stainless Steel	9 mm	14 mm	4.5 mm	Shielded	703 N	337 N	32.4	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
689	52100 Chrome Steel	9 mm	17 mm	4 mm	Open	1128 N	534 N	36	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
679zz	52100 Chrome Steel	9 mm	14 mm	4.5 mm	Shielded	781 N	374 N	36	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S679 2rs	440C Stainless Steel	9 mm	14 mm	4.5 mm	Sealed	703 N	337 N	32.4	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
679 2rs	52100 Chrome Steel	9 mm	14 mm	4.5 mm	Sealed	781 N	374 N	36	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S679	440C Stainless Steel	9 mm	14 mm	3 mm	Open	703 N	337 N	32.4	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
679	52100 Chrome Steel	9 mm	14 mm	3 mm	Open	781 N	374 N	36	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S639zz	440C Stainless Steel	9 mm	30 mm	10 mm	Shielded	3564 N	1498 N	21.6	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
639zz	52100 Chrome Steel	9 mm	30 mm	10 mm	Shielded	3960 N	1664 N	24	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S639 2rs	440C Stainless Steel	9 mm	30 mm	10 mm	Sealed	3564 N	1498 N	21.6	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S639	440C Stainless Steel	9 mm	30 mm	10 mm	Open	3564 N	1498 N	21.6	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
639 2rs	52100 Chrome Steel	9 mm	30 mm	10 mm	Sealed	3960 N	1664 N	24	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
639	52100 Chrome Steel	9 mm	30 mm	10 mm	Open	3960 N	1664 N	24	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S629zz	440C Stainless Steel	9 mm	26 mm	8 mm	Shielded	3491 N	1427 N	25.2	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
629zz	52100 Chrome Steel	9 mm	26 mm	8 mm	Shielded	3879 N	1586 N	28	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S629 2rs	440C Stainless Steel	9 mm	26 mm	8 mm	Sealed	3491 N	1427 N	25.2	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
629 2rs	52100 Chrome Steel	9 mm	26 mm	8 mm	Sealed	3879 N	1586 N	28	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S629	440C Stainless Steel	9 mm	26 mm	8 mm	Open	3491 N	1427 N	25.2	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
629	52100 Chrome Steel	9 mm	26 mm	8 mm	Open	3879 N	1586 N	28	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S609zz	440C Stainless Steel	9 mm	24 mm	7 mm	Shielded	2568 N	1040 N	28.8	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
609zz	52100 Chrome Steel	9 mm	24 mm	7 mm	Shielded	2853 N	1155 N	32	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S609 2rs	440C Stainless Steel	9 mm	24 mm	7 mm	Sealed	2568 N	1040 N	28.8	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant

Metric Standard

609 2rs	52100 Chrome Steel	9 mm	24 mm	7 mm	Sealed	2853 N	1155 N	32	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
609	52100 Chrome Steel	9 mm	24 mm	7 mm	Open	2853 N	1155 N	32	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
S609	440C Stainless Steel	9 mm	24 mm	7 mm	Open	2568 N	1040 N	28.8	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMR148zz	440C Stainless Steel	8 mm	14 mm	4 mm	Shielded	626 N	278 N	34.2	Metric	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant