

SSUCFC SERIES



Номер детали	Размер шахты	L	J	H3	Базовые характеристики нагрузки ст	Базовые характеристики нагрузки Cor	Material	Precision	ISO 9001	Rohs	Clearance
Ssucfc207	SSFC207	SSUC207	35 mm	135 mm 5-5/16 in	110 mm 4-21/64 in	90 mm 3.5433 in	21.8 kN 4901 lbf	12.3 kN 2765 lbf	Stainless	P0	YES
Ssucfc207 22	SSFC207	SSUC207-22	1-3/8 in	135 mm 5-5/16 in	110 mm 4-21/64 in	90mm35433in	21.8 kN 4901 lbf	12.3 kN 2765 lbf	Stainless	P0	YES
Ssucfc207 21	SSFC207	SSUC207-21	1-5/16 in	135 mm 5-5/16 in	110 mm 4-21/64 in	90mm35433in	21.8 kN 4901 lbf	12.3 kN 2765 lbf	Stainless	P0	YES
Ssucfc207 20	SSFC207	SSUC207-20	1-1/4 in	135 mm 5-5/16 in	100.4 mm 4-21/64 in	90 mm 3. 5433 in	21.8 kN 4901 lbf	12.3 kN 2765 lbf	Stainless	P0	YES
Ssucfc206 20	SSFC206	SSUC206-20	1-1/4 in	125 mm 4-29/32 in	100.3 mm 3-15/16 in	80 mm 3.1496 in	16.5 kN 3709 lbf	9.05 kN 2035 lbf	Stainless	P0	YES
Ssucfc206 19	SSFC206	SSUC206-19	1-3/16 in	125 mm 4-29/32 in	100.2 mm 3-15/16 in	80 mm 3.1496 in	16.5 kN 3709 lbf	9.05 kN 2035 lbf	Stainless	P0	YES
Ssucfc206	SSFC206	SSUC206	30 mm	125 mm 4-29/32 in	100.1 mm 3-15/16 in	80 mm 3.1496 in	16.5 kN 3709 lbf	9.05 kN 2035 lbf	Stainless	P0	YES
Ssucfc206 18	SSFC206	SSUC206-18	1-1/8 in	125 mm 4-29/32 in	100 mm 3-15/16 in	80 mm 3.1496 in	16.5 kN 3709 lbf	9.05 kN 2035 lbf	Stainless	P0	YES
Ssucfc206 17	SSFC206	SSUC206-17	1-1/16 in	125 mm 4-29/32 in	100.2 mm 3-15/16 in	80 mm 3.1496 in	16.5 kN 3709 lbf	9.05 kN 2035 lbf	Stainless	P0	YES
Ssucfc205 16	SSFC205	SSUC205-16	1 in	115 mm 4-17/32 in	90 mm 3-35/64 in	70 mm 2.7559 in	11.9 kN 2675 lbf	6.3 kN 1416 lbf	Stainless	P0	YES
Ssucfc205	SSFC205	SSUC205	25 mm	115 mm 4-17/32 in	90 mm 3-35/64 in	70 mm 2.7559 in	11.9 kN 2675 lbf	6.3 kN 1416 lbf	Stainless	P0	YES
Ssucfc205 15	SSFC205	SSUC205-15	15/16 in	115 mm 4-17/32 in	90 mm 3-35/64 in	70 mm 2.7559 in	11.9 kN 2675 lbf	6.3 kN 1416 lbf	Stainless	P0	YES

SSUCFC SERIES

Ssucfc205 14	SSFC205	SSUC205-14	7/8 in	115 mm 4-17/32 in	90 mm 3-35/64 in	70 mm 2.7559 in	11.9 kN 2675 lbf	6.3 kN 1416 lbf	Stainless	P0	YES
Ssucfc205 13	SSFC205	SSUC205-13	13/16 in	115 mm 4-17/32 in	90 mm 3-35/64 in	70 mm 2.7559 in	11.9 kN 2675 lbf	6.3 kN 1416 lbf	Stainless	P0	YES
Ssucfc204	SSFC204	SSUC204	20 mm	100 mm 3-15/16 in	78 mm 3-5/64 in	62 mm 2. 4409 in	10.9 kN 2450 lbf	5.35 kN 1203 lbf	Stainless	P0	YES
Ssucfc204 12	SSFC204	SSUC204-12	3/4 in	100 mm 3-15/16 in	78 mm 3-5/64 in	62 mm 2. 4409 in	10.9 kN 2450 lbf	5.35 kN 1203 lbf	Stainless	P0	YES
Ssucfc207 23	SSFC207	SSUC207-23	1-7/16 in	135 mm 5-5/16 in	110 mm 4-21/64 in	90 mm 3.5433 in	21.8 kN 4901 lbf	12.3 kN 2765 lbf	Stainless	P0	YES
Ssucfc208 24	SSFC208	SSUC208-24	1-1/2 in	145 mm 5-23/32 in	120 mm 4-23/32 in	100 mm 3.9370 in	24.8 kN 5575 lbf	14.3 kN 3215 lbf	Stainless	P0	YES
Ssucfc208 25	SSFC208	SSUC208-25	1-9/16 in	145 mm 5-23/32 in	120 mm 4-23/32 in	100 mm 3.9370 in	24.8 kN 5575 lbf	14.3 kN 3215 lbf	Stainless	P0	YES
Ssucfc208	SSFC208	SSUC208	40 mm	145 mm 5-23/32 in	120 mm 4-23/32 in	100 mm 3.9370 in	24.8 kN 5575 lbf	14.3 kN 3215 lbf	Stainless	P0	YES