

Angular Contact Spherical Plain Bearings



Номер детали	ID	OD	Нормальная ширина	Ширина OD	Угол наклона	Material	Динамическая нагрузка	Статическая нагрузка	Lubrication	RoHS	REACH	Clearance
GAC 25 F	25 mm	47 mm	15 mm	14 mm	2.7°	Steel/PTFE FRP	5400 lbf	8550 lbf	Required	Compliant	Compliant	C2/C0/C3
GAC 30 F	30 mm	55 mm	17 mm	15 mm	4.7°	Steel/PTFE FRP	6750 lbf	10800 lbf	Required	Compliant	Compliant	C2/C0/C3
GAC 35 F	35 mm	62 mm	18 mm	16 mm	3.9°	Steel/PTFE FRP	7987.5 lbf	12825 lbf	Required	Compliant	Compliant	C2/C0/C3
GAC 40 F	40 mm	68 mm	19 mm	17 mm	3.7°	Steel/PTFE FRP	9900 lbf	15637.5 lbf	Required	Compliant	Compliant	C2/C0/C3
GAC 45 F	45 mm	75 mm	20 mm	18 mm	3.4°	Steel/PTFE FRP	11250 lbf	18000 lbf	Required	Compliant	Compliant	C2/C0/C3
GAC 50 F	50 mm	80 mm	20 mm	19 mm	1.6°	Steel/PTFE FRP	13162.5 lbf	20925 lbf	Required	Compliant	Compliant	C2/C0/C3
GAC 60 F	60 mm	95 mm	23 mm	21 mm	2.6°	Steel/PTFE FRP	17550 lbf	28125 lbf	Required	Compliant	Compliant	C2/C0/C3
GAC 70 F	70 mm	110 mm	25 mm	23 mm	2.3°	Steel/PTFE FRP	22050 lbf	35100 lbf	Required	Compliant	Compliant	C2/C0/C3
GAC 80 F	80 mm	125 mm	29 mm	25.5 mm	3.5°	Steel/PTFE FRP	27450 lbf	43425 lbf	Required	Compliant	Compliant	C2/C0/C3
GAC 90 F	90 mm	140 mm	32 mm	28 mm	2.9°	Steel/PTFE FRP	32850 lbf	53100 lbf	Required	Compliant	Compliant	C2/C0/C3
GAC 100 F	100 mm	150 mm	32 mm	31 mm	0.8°	Steel/PTFE FRP	41850 lbf	67500 lbf	Required	Compliant	Compliant	C2/C0/C3
GAC 110 F	110 mm	170 mm	38 mm	34 mm	3°	Steel/PTFE FRP	49500 lbf	77625 lbf	Required	Compliant	Compliant	C2/C0/C3
GAC 120 F	120 mm	180 mm	38 mm	37 mm	0.7°	Steel/PTFE FRP	58500 lbf	93375 lbf	Required	Compliant	Compliant	C2/C0/C3