

SJM-T SERIES



Номер детали	d	B	C1	d2	d3 UNF 2B	h	l1	L2	Диаметр шарика мм (дюйм)	α° mis angle	Система измерений	Material	Температурный диапазон	RoHS	ISO: 9001	Радиальный клиренс
Sjm 6t	0.375	0.5	0.416	1.025	37857	1.938	1.187	2.45	0.687	12	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sjm 5t	0.3125	0.437	0.327	0.9	5/16-24	1.875	1.187	2.325	0.593	14	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sjm 4t	0.25	0.437	0.337	0.806	37009	1.562	0.968	1.964	0.531	16	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sjm 12t	0.75	0.875	0.64	1.775	38582	2.875	1.687	3.762	1.25	14	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sjm 10t	0.625	0.75	0.577	1.525	37727	2.625	1.562	3.387	1.062	16	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sjm 7t	0.4375	0.562	0.452	1.15	7/16-20	2.125	1.281	2.7	0.781	14	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sjm 8t	0.5	0.625	0.515	1.337	36942	2.438	1.468	3.106	0.875	12	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard