


Stainless Large Size Flanged Ball Bearings



Номер детали	ID	OD	Width	Flange OD	Ширина фланца	Тип щита	Динамическая нагрузка	Статическая нагрузка	Максимальная скорость (X1000 об/мин)	Материал кольца	Система измерений	Тип подшипника	Construction	Температурный диапазон	Оценка точности	Clearance	RoHS	SGS
SF6905ZZ	25 mm	42 mm	9 mm	45 mm	2 mm	Shielded	1418 lbf	921 lbf	14.4	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6905	25 mm	42 mm	9 mm	45 mm	2 mm	Open	1418 lbf	921 lbf	14.4	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6805ZZ	25 mm	37 mm	7 mm	40 mm	1.5 mm	Shielded	870 lbf	595 lbf	16.2	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6805	25 mm	37 mm	7 mm	40 mm	1.5 mm	Open	87 lbf	595 lbf	16.2	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6705	25 mm	32 mm	4 mm	34 mm	1 mm	Open	22 lbf	170 lbf	6.3	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF63805ZZ	25 mm	37 mm	10 mm	40 mm	2 mm	Shielded	871 lbf	593 lbf	16.2	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF63805	25 mm	37 mm	10 mm	40 mm	2 mm	Open	871 lbf	593 lbf	16.2	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6904ZZ	20 mm	37 mm	9 mm	40 mm	2 mm	Shielded	1291 lbf	745 lbf	17.1	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6904	20 mm	37 mm	9 mm	40 mm	2 mm	Open	1291 lbf	745 lbf	17.1	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6804ZZ	20 mm	32 mm	7 mm	35 mm	1.5 mm	Shielded	813 lbf	498 lbf	18.9	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6704	20 mm	27 mm	4 mm	28 mm	0.8 mm	Open	204 lbf	15 lbf	7.7	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6804	20 mm	32 mm	7 mm	35 mm	1.5 mm	Open	813 lbf	498 lbf	18.9	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF63804ZZ	20 mm	32 mm	10 mm	35 mm	2 mm	Shielded	812 lbf	498 lbf	18.9	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF63804	20 mm	32 mm	10 mm	35 mm	2 mm	Open	812 lbf	498 lbf	18.9	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6903ZZ	17 mm	30 mm	7 mm	32.5 mm	1.5 mm	Shielded	929 lbf	518 lbf	19.8	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6903	17 mm	30 mm	7 mm	32 mm	1.5 mm	Open	929 lbf	518 lbf	19.8	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6803ZZ	17 mm	26 mm	5 mm	28 mm	1.1 mm	Shielded	451 lbf	295 lbf	21.6	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6803	17 mm	26 mm	5 mm	28 mm	1.1 mm	Open	451 lbf	295 lbf	21.6	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6703ZZ	17 mm	23 mm	4 mm	24.5 mm	0.8 mm	Shielded	202 lbf	133 lbf	8.55	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6703	17 mm	23 mm	4 mm	24 mm	0.8 mm	Open	202 lbf	133 lbf	8.6	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF63803ZZ	17 mm	26 mm	7 mm	28 mm	1.5 mm	Shielded	451 lbf	295 lbf	21.6	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF63803	17 mm	26 mm	7 mm	28 mm	1.5 mm	Open	451 lbf	295 lbf	21.6	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6902ZZ	15 mm	28 mm	7 mm	30.5 mm	1.5 mm	Shielded	876 lbf	455 lbf	21.6	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6902	15 mm	28 mm	7 mm	30 mm	1.5 mm	Open	876 lbf	455 lbf	21.6	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6802ZZ	15 mm	24 mm	5 mm	26 mm	1.1 mm	Shielded	419 lbf	255 lbf	23.4	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant

Stainless Large Size Flanged Ball Bearings

SF6802	15 mm	24 mm	5 mm	26 mm	1.1 mm	Open	419 lbf	255 lbf	23.4	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6702ZZ	15 mm	21 mm	4 mm	22.5 mm	0.8 mm	Shielded	190 lbf	118 lbf	9.9	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF6702	15 mm	21 mm	4 mm	22 mm	0.8 mm	Open	190 lbf	118 lbf	9.9	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF63802ZZ	15 mm	24 mm	7 mm	26 mm	1.5 mm	Shielded	419 lbf	255 lbf	23.4	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant
SF63802	15 mm	24 mm	7 mm	26 mm	1.5 mm	Open	419 lbf	255 lbf	23.4	440C Stainless Steel	Metric	Ball	Single Row	-30° to 110°C	ABEC-1/P0	C0	Compliant	Compliant